

uSD-1216 Adapter Board

for AW-NM191-uSD and AW-CM276-uSD

User Guide

Rev. E

(For Standard)

Revision History

Version	Revision Date	Description	Initials	Approved
A	2020/05/14	<ul style="list-style-type: none"> ● Initial Version 	Renton Tao	N.C. Chen
B	2020/05/28	<ul style="list-style-type: none"> ● Update VIO and VIO_SD configuration 	Renton Tao	N.C. Chen
C	2020/6/5	<ul style="list-style-type: none"> ● Add 3. PCM UART extension ● Update 4. EVB Kits Contents 	Renton Tao	N.C. Chen
D	2020/7/20	<ul style="list-style-type: none"> ● Add Block Diagram of AW-NM191-uSD 	Renton Tao	N.C. Chen
E	2020/8/17	<ul style="list-style-type: none"> ● Update 2.3 Schematics and 2.4 Placement ● Update the photo of 2.2 HW introduction ● Remove the content of PCM UART extension adapter board in 3. EVB Kits Contents ● Add Block Diagram of AW-CM276-uSD 	Renton Tao	N.C. Chen

Table of Content

1. Introduction	4
1.1 Supported I/O to host	4
1.2 Supported I/O signal level.....	4
1.3 Supported RF standards.....	4
2. uSD-1216 Adapter Board	5
2.1 Block Diagram	5
2.2 HW Introduction.....	6
2.3 Schematics.....	8
2.4 Placement	10
3. EVB Kits Contents	12

1. Introduction

Azurewave provides uSD-1216 adapter board with Wi-Fi/BT module solutions for NXP i.MX RT and i.MX6 Evaluation Kits. The uSD-1216 adapter board supports AW-NM191NF (w/ NXP W8801) and AW-CM276NF (w/ NXP W8997) Wi-Fi combo BT module solutions.

- Wi-Fi through uSD interface is for AW-NM191NF and AW-CM276NF
- BT through uSD is only for AW-CM276NF.

Main chip	AzureWave Module	uSD Adaptor Board
NXP W8801	AW-NM191NF	AW-NM191-uSD
NXP W8997	AW-CM276NF	AW-CM276-uSD

1.1 Supported I/O to host

- Micro SD (uSD) interface for Wi-Fi or Wi-Fi/BT.
- Arduino headers for Bluetooth through UART interface.
- FFC connector for UART, PCM, and other control signal.
- Embedded UART-to-USB IC as an option for UART.
- Other debug and power interface.

1.2 Supported I/O signal level

I/O\ voltage level	1.8V	3.3V
SDIO(3.0/2.0)	V	V
UART	N/A	V

1.3 Supported RF standards


Model \ Standards	Wi-Fi*	BT*
AW-NM191NF	1x1 Wi-Fi 4	N/A
AW-CM276NF	2x2 Wi-Fi 5 (2.4/5GHz)	5.0

*Connecting with i-pex gen 4 RF connector

2. uSD-1216 Adapter Board


2.1 Block Diagram

For AW-NM191-uSD



AW-NM191-uSD Block Diagram

For AW-CM276-uSD



AW-CM276NF-uSD Block diagram

2.2 HW Introduction


VIO_SD voltage level options

- For 3.3V supply, please connect J11 (2-3).
- For 1.8V supply, please connect J11 (1-2).

VIO voltage level options

- For 3.3V supply, please connect J4 (2-3).
- For 1.8V supply, please connect J4 (1-2).

UART signal and 3.3V power source is configured from FFC connector at BOT side as default.






By using headers for Bluetooth through UART interface

- UART_RTS: J7 (pin 3) or J10 (pin 6)
- UART_TXD: J8 (pin 1) or J10 (pin 4)
- UART_CTS: J7 (pin 4) or J10 (pin 8)
- UART_RXD: J8 (pin 2) or J10 (pin 2)


By using headers for Bluetooth audio through PCM interface

- PCM_IN: J13 (pin 1)
- PCM_OUT: J13 (pin 2)
- PCM_SYNC: J13 (pin 3)
- PCM_CLK: J13 (pin 4)






2.4 Placement




TOP View



BOT View

3. EVB Kits Contents

Content	Description
	<p>AW-NM191-uSD or AW-CM276-uSD</p>
	<p>75mm, 20 contacts, 0.5mm pitch FFC Cable</p>
	<p>PIFA Antenna</p> <ul style="list-style-type: none"> ● Radiation: Directional ● 3D Peak Gain: <ul style="list-style-type: none"> ■ 2.98dBi (2.4~2.5GHz) ■ 5.16dBi (4.9~5.9GHz) ● Polarization: Linear Vertical ● Connector: IPEX-4 Compatible ● Operating Temp: -20°C ~ +65°C ● Storage Temp: -30°C ~ +75°C